

Utförande: Lackerad aluminium och metall. Bländskydd av matt akryl.

T5 cirkellysrör.

Montage: Delinfäld i tak. Montageplåt för mjuka undertak finns som tillbehör.

Anslutning: Snabbkopplingsplint 5x4mm². Överkopplingsbar.

Design: Fredrik Mattson 2010.

W	D	FÄRG/FINISH	ART
22W/2Gx13	330	Vit/White	7971-1-01
22W/2Gx13	330	Vit/White	7971-1-01HFF
22W/2Gx13	330	Multi/Multi	7971-1-90
22W/2Gx13	330	Multi/Multi	7971-1-90HFF
40W/2Gx13	475	Vit/White	7971-3-01
40W/2Gx13	475	Vit/White	7971-3-01HFF
40W/2Gx13	475	Multi/Multi	7971-3-90
40W/2Gx13	475	Multi/Multi	7971-3-90HFF
55W/2Gx13	475	Vit/White	7971-4-01
55W/2Gx13	475	Vit/White	7971-4-01HFF
55W/2Gx13	475	Multi/Multi	7971-4-90
55W/2Gx13	475	Multi/Multi	7971-4-90HFF

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim






TILLBEHÖR/ACCESSORIES	Art
Montagebrygga för mjuka tak 330/	97400-1-01
Support-frame for soft ceilings	
Montagebrygga för mjuka tak 500/	97400-3-01
Support-frame for soft ceilings	

Finish: Painted aluminum and metal. Diffuser in matt acrylic. T5 circular tube.

Installation: Partly recessed. Support-frame for plaster ceilings available as accessory.

Connection: Terminal block 5x4mm². Two entry holes.

Design: Fredrik Mattson.



PENDLARI/PENDANTS 82-83



VÄGG/WALL 122



BORD/TABLE 154



UTOMHUS/OUTDOOR 180-181

